


NOTES:

1. ASPHALT THICKNESS SHALL MATCH THE EXISTING ASPHALT THICKNESS OR BE 2" NC DOT S9.5B ASPHALT WHICHEVER IS GREATER.
2. ALL PAVEMENT CUTS SHALL BE REPAIRED WITHIN 3 DAYS FROM THE DATE THAT THE ASPHALT IS CUT FOR THE REPAIR.
3. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING COMPACTION REQUIREMENTS BY A LICENSED GEO-TECHNICAL FIRM.
4. ALL PAVEMENT PATCHES SHALL PROVIDE A UNIFORM AND SMOOTH DRIVING SURFACE.
5. THE CONTRACTOR SHALL REMOVE ANY UNSUITABLE MATERIAL FROM THE PATCH AREA AS DIRECTED BY THE TOWN ENGINEER AND REPLACE WITH A SUITABLE MATERIAL.
6. SUITABLE MATERIAL SHALL BE FREE FROM HEAVY CLAYS, GUMBO, DEBRIS, ORGANICS, AND LITTLE TO NO EXCESSIVE MOISTURE.
7. SUITABLE FILL SHALL BE INSTALLED IN 6" - 8" LIFTS COMPACTED BY A MECHANIZED TAMPER.

SECTION: STREETS	PAVEMENT REPAIR FULL DEPTH PATCH	PUBLIC SERVICES DEPARTMENT
DATE: 2021		 Town of Leland
DRAWN BY: JWP		DETAIL NO. ST - 02
CHECKED BY: TOWN PSD		
SCALE: NOT TO SCALE		