



1. ASPHALT THICKNESS SHALL MATCH THE EXISTING ASPHALT THICKNESS OR BE 2" NC DOT S9.5B ASPHALT WHICHEVER IS GREATER.
2. ALL PAVEMENT CUTS SHALL BE REPAIRED WITHIN 3 DAYS FROM THE DATE THAT THE ASPHALT IS CUT FOR THE REPAIR.
3. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING COMPACTION REQUIREMENTS BY A LICENSED GEO-TECHNICAL FIRM.
4. ALL PAVEMENT PATCHES SHALL PROVIDE A UNIFORM AND SMOOTH DRIVING SURFACE.
5. SUITABLE MATERIAL SHALL BE FREE FROM HEAVY CLAYS, GUMBO, DEBRIS, ORGANICS, AND LITTLE TO NO EXCESSIVE MOISTURE.
6. SUITABLE FILL SHALL BE INSTALLED IN 6" - 8" LIFTS COMPACTED BY A MECHANIZED TAMPER.

SECTION: STREETS	<b>PAVEMENT REPAIR UTILITY CUT</b>	PUBLIC SERVICES DEPARTMENT
DATE: 2021		 <b>Town of Leland</b>
DRAWN BY: JWP		
CHECKED BY: TOWN PSD		
SCALE: NOT TO SCALE		